

SUPPLIER/FACTORY	FACTORY DIRECTION	PRODUCT	REFERENCES (Certificate)	CERTIFICATE	EXPIRY DATE
BASELL POLYOLEFINE GmbH	WESSELING (Alemania)	Black polyethylene PE 100 compound for the supply of gaseous fuels	TRADEMARK: HOSTALEN CRP100 BLACK TECHNICAL CHARACTERISTICS: IF = 0,23 g/10 min ; Densidad / Density = 959 Kg/m³ APPLICATION: MOP <= 26,7 bar (Pc (0°C) >= 10,4 bar; Ø 250 SDR 11)	001 / 003499	26/09/2025
BASELL POLYOLEFINE GmbH	WESSELING (Alemania)	Black polyethylene PE 100 compound for the supply of gaseous fuels	TRADEMARK: HOSTALEN CRP100 RESIST CR BLACK TECHNICAL CHARACTERISTICS: IF = 0,23 g/10 min ; Densidad / Density = 958 Kg/m³ APPLICATION: MOP <= 25,73 bar (Pc (0°C) >= 10 bar ; Ø 250 SDR 11)	001 / 005137	18/02/2025
BOREALIS AG // BOREALIS AB	Stenungsund - (Suecia)	Black polyethylene PE 100-RC compound for the supply of gaseous fuels	TRADEMARK: BORSAFE HE3490-LS-HW CARACTERISTICAS TÉCNICAS: IF = 0,22 g/10 min ; Densidad = 957 Kg/m³ INDICACION DE USO: MOP <= 25,73 bar (Pc (0°C) >= 10 bar ; Ø 250 SDR 11)	001 / 007647	10/10/2029
BOREALIS AG // BOREALIS AB	Stenungsund - (Suecia)	Black polyethylene PE 100 compound for the supply of gaseous fuels	TRADEMARK: BORSAFE HE3490-LS-HW TECHNICAL CHARACTERISTICS: IF = 0,22 g/10 min ; Densidad = 957 Kg/m³ APPLICATION: MOP <= 25,73 bar (Pc (0°C) >= 10 bar ; Ø 250 SDR 11)	001 / 007530	21/09/2028
BOREALIS AG // BOREALIS AB	Stenungsund - (Suecia)	Black polyethylene PE 100 compound for the supply of gaseous fuels	TRADEMARK: BORSAFE HE3490-LS TECHNICAL CHARACTERISTICS: IF = 0,25 g/10 min ; Densidad = 960 Kg/m³ APPLICATION: MOP <= 25,73 bar (Pc (0°C) >= 10 bar ; Ø 250 SDR 11)	001 / 005970	10/04/2028
HANWHA TOTALENERGIES PETROCHEMICAL CO., LTD.	SEOSAN-SI (Corea del Sur)	Black polyethylene PE 100 compound for the supply of gaseous fuels	TRADEMARK: HDPE XS10B PE100 black TECHNICAL CHARACTERISTICS: IF = 0,28 g/10 min ; Densidad / Density = 959 Kg/m³ APPLICATION: MOP <= 26,5 bar (Pc (0°C) >= 10,3 bar	001 / 007415	10/08/2027
HYOSUNG TNC CORPORATION // KOREA PETROCHEMICAL IND. CO., LTD.	NAM-GU, ULSAN (Corea del Sur)	Black polyethylene PE 100 compound for the supply of gaseous fuels	TRADEMARK: P600BL TECHNICAL CHARACTERISTICS: IF = 0,23 g/10 min ; Densidad = 961 Kg/m³ APPLICATION: MOP <= 9,4 bar (Pc (0°C) >= 3,2 Bar ; Ø 250 SDR 11)	001 / 007112	06/07/2025
INEOS SERVICES BELGIUM N.V. // INEOS MANUFACTURING BELGIUM, N.V.	ANTWERPEN (Bélgica)	Black polyethylene PE 100 compound for the supply of gaseous fuels	TRADEMARK: ELTEX SUPERSTRESS TUB121N6000 TECHNICAL CHARACTERISTICS: IF = 0,29 g/10 min ; Densidad / Density = 959 Kg/m³ APPLICATION: MOP <= 26,2 bar (Pc (0°C) >= 10,2 bar; Ø 250 SDR 11)	001 / 007594	25/04/2029
INEOS SERVICES BELGIUM N.V. // INEOS MANUFACTURING BELGIUM, N.V.	ANTWERPEN (Bélgica)	Black polyethylene PE 100 compound for the supply of gaseous fuels	TRADEMARK: ELTEX SUPERSTRESS TUB121N9000 TECHNICAL CHARACTERISTICS: IF = 0,24 g/10 min ; Densidad / Density = 959 Kg/m³ APPLICATION: MOP <= 25,73 bar (Pc (0°C) >= 10 bar ; Ø 250 SDR 11)	001 / 006773	08/11/2027
INEOS SERVICES BELGIUM N.V. // INEOS MANUFACTURING BELGIUM, N.V.	ANTWERPEN (Bélgica)	Black polyethylene PE 100 compound for the supply of gaseous fuels	TRADEMARK: ELTEX TUB 121 N 3000 TECHNICAL CHARACTERISTICS: IF = 0,26 g/10 min ; Densidad = 960 Kg/m³ APPLICATION: MOP <= 25,73 bar (Pc (0°C) >= 10 bar ; Ø 250 SDR 11)	001 / 006075	04/10/2029
REPSOL QUÍMICA, S.A. // REPSOL POLIMEROS UNIPESOAL, LDA.	SINES (Portugal)	Black polyethylene PE 100 compound for the supply of gaseous fuels	TRADEMARK: ALCUDIA T-100-NLS TECHNICAL CHARACTERISTICS: IF = 0,27 g/10 min ; Densidad / Density = 962 Kg/m³ APPLICATION: MOP <= 25,73 bar (Pc (0°C) >= 10 bar ; Ø 250 SDR 11)	001 / 007539	05/04/2026
REPSOL QUÍMICA, S.A. // REPSOL POLIMEROS, LDA.	SINES (Portugal)	Black polyethylene PE 100 compound for the supply of gaseous fuels	TRADEMARK: ALCUDIA T-100-NLS TECHNICAL CHARACTERISTICS: IF = 0,27 g/10 min ; Densidad / Density = 962 Kg/m³ APPLICATION: MOP <= 25,73 bar (Pc (0°C) >= 10 bar ; Ø 250 SDR 11)	001 / 006161	05/04/2026
SABIC PETROCHEMICALS, B.V. // SABIC SAUDI KAYAN	JUBAIL INDUSTRIAL CITY (Arabia Saudita)	Black polyethylene PE 100 compound for the supply of gaseous fuels	TRADEMARK: SABIC HDPE P 6006AD 10000 TECHNICAL CHARACTERISTICS: IF = 0,23 g/10 min ; Densidad / Density = 957 Kg/m³ APPLICATION: MOP <= 26,45 bar (Pc (0°C) >= 10,3 bar; Ø 250 SDR 11)	001 / 007430	26/09/2027
SABIC POLYOLEFINE GmbH	GELSENKIRCHEN (Alemania)	Black polyethylene PE 100 compound for the supply of gaseous fuels	TRADEMARK: SABIC Vestolen A RELY 5924 R 10000 TECHNICAL CHARACTERISTICS: IF = 0,22 g/10 min ; Densidad = 959 Kg/m³ APPLICATION: MOP <= 8,45 bar (Pc (0°C) >= 2,8 Bar ; Ø 250 SDR 11)	001 / 007026	13/02/2025
SAFRIPOL (PTY) LTD.	SASOLBURG (Sudáfrica)	Black polyethylene PE 100 compound for the supply of gaseous fuels	TRADEMARK: iMPACT 100 TECHNICAL CHARACTERISTICS: IF = 0,30 g/10 min ; Densidad / Density = 957 Kg/m³ APPLICATION: MOP <= 26,2 bar (Pc (0°C) >= 10,2 bar	001 / 007446	14/10/2027